



Koleshvari Infratech Pvt. Ltd.

www.acodor.in

Plot No. 298, Road No. 4, GIDC, Kathawada, Ahmedabad, Gujarat 38243



Email : info@acodor.in


Mob : +91 76220 23093

2 hours Fire Door Specification with rate - Glazed fire door

1	Fire Rated Doors - Galvanised Steel Fire Rated Fully Glazed Doors -2hr				
frame	Providing and fixing fire resistant door frame of section 50 x 60 mm on horizontal side & 35 x 60 mm on vertical sides having built in rebate made out of 1.6 mm thick GI sheet (Zinc coating not less than 120gm/m ²) suitable for mounting 120 min Fire Rated Glazed Door Shutters. The frame shall be filled with Mineral wool Insulation having density min 96Kg/m ³ / Honey Comb Cre . The frame will have a provision of G.I. Anchor fastners 14 nos as per acodor standard (5 each on vertical style & 4 on horizontal style of size M10 x 80) suitable for fixing in the opening along with Factory made Template for SS Ball Bearing Hinges of Size 100x75x3mm for fixing of fire rated glazed shutter . The frame shall be finished with a approved Powder coating of not less than 50 micron in desired shade as per the directions of Engineer - in- charge . The manufacturer company must be ISO 9001-2015 cerified by TUV NORD .				
shutter	Providing and fixing 60 mm thick glazed fire resistant door shutters of 120 min Fire Rating confirming to IS:3614 (Part II) / BS-476 Part 20 & 22 or EN1634-1:1999, tested In and certified as per NABL Approved Lab , with suitable mounting on door frame, consisting of vertical styles, top rail & side rail 60 mm x 60 mm wide and bottom rail of 110 mm x 60 mm made out of 1.2mm thick G.I. sheet (zinc coating not less than 120gm/m ²) duly filled mineral wool insulation having density min 96 kg/m ³ / Honeycomb core and fixing with necessary stainless steel ball bearing hinges of size 100x89x3mm of approved make, including applying a coat of approved fire resistant primer or powder coating not less than 30 micron etc all complete as per direction of Engineer-in-charge (panelling to be paid for seperately). The manufacturer company must be ISO 9001-2015 cerified by TUV .				
partion with glass	Providing and fixing glazing in fire resistant door shutters, fixed panels& partitions etc., with G.I. beading made out of 1.6 mm thick G.I. sheet Powder coating of size 20 x 33 mm screwed with M4 x 38 mm SS screws at distance 75 mm from the edges and 150 mm c/c , including applying a coat of approved powder coating of not less than 60 micron on G.I. beading, & special ceramic tape of 5 x 20 mm size etc complete in all respect as per NBC2016, IS 16231 (Part 3):2016 and as per direction of Engineer-incharge with glass of required thickness having 120 minutes of bi-directional fire resistance both integrity & radiation control (EW120) and minimum 20 minutes of insulation (EI20). The manufacturer have to give test report/certification of fire glass and the glass should have the stamp showing the value of E, EW & EI. The glass shall be tested in approved NABL accredited lab or by any other accreditation body which operates in accordance with ISO/IEC 17011 and accredits labs as per ISO/IEC 17025 for testing and calibration scopes shall be eligible. The maximum glazing size shall not be more than 1100x2200 mm (w x h) or 2.42 sqm.				

Annexure III: Commercial Terms & Conditions

Prices	The above quoted prices are net for delivery at Ex factory Ahmedabad
Size	Door size will be 5 to 10 mm smaller then Actual Dimension
Taxes	Duties taxes and other Government levies quoted are as per the current rates applicable. However, the rates prevailing at the time of dispatch will be charged.

Payment	50 % advance along with your technically and commercially clear purchase order and balance 50% before dispatch of the material from the factory on pi.	
Delivery	3 to 4 weeks Days from the date of receipt of your technically and commercially clear purchase order (likely to vary depending upon the order quantity), subject to force majeure conditions.	
Unloading	Materials will be unloaded only at ground levels, any shifting of materials to other levels as per Actual or in client scope .	
Storage & Security	Storage and security of material on receipt at your site shall be at clients responsibility.	
Validity	180 days and subject to confirmation thereafter.	
Transportation	An actual.	
Note	An Order will be considered technically clear only on receipt of the following information:	
	(i) Quote is as per the Breakup provided by us and in case of any changes in dimensions and Quantities apart from the breakup it will be charged as per Actual.	
	(ii) Hardware value quoted in this quotation is only with our door package and the Price will not be the same when you Purchase Same Hardware individually.	
Thanking you		
Sincerely,		
For KOLESHVARI INFRATECH PVT LTD		